


## Yoke type track roller CRY28-VR-IKO - CRY28-VR-IKO

<https://www.123bearing.eu/bearing-housing/roller-bearing/yoke-track-roller/cry28-vr-iko>

**IKO**  
**ROLLER FOLLOWERS**  
Non-separable Roller Followers, Inch Series **Full Complement Type /With Inner Ring**



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions: mm(inch)									
	Shield type Cylindrical outer ring	Sealed type Cylindrical outer ring		d	D	B	C						
<b>12.700</b> (1/2)	<b>CRY 28 VR</b>		290	12.700 (1/2)	44.450 (1 3/4)	26.988 (1.0625)	25.400 (1)						
				Shaft dia.				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>				
				Push fit		Drive fit		Press fit					
				Min.	Max.	Min.	Max.	Min.	Max.				
				32.7(1.287)	500 (20)	12.682	12.692	12.698	12.708	12.708	12.718	35 300	55 600

Remarks: 1. The inner ring has an oil hole.  
2. Provided with prepacked grease.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952398877
Inside diameter	12.7 mm
Inside diameter	1/2" inch
Outside diameter	44.45 mm
Outside diameter	1 3/4" inch
Thickness	26.988 mm
Thickness	1 1/16" inch
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE