


Yoke type track roller CRY30-VR-IKO - CRY30-VR-IKO

<https://www.123bearing.eu/bearing-housing/roller-bearing/yoke-track-roller/cry30-vr-iko>

IKO
ROLLER FOLLOWERS
Non-separable Roller Followers, Inch Series **Full Complement Type/With Inner Ring**



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions: mm(inch)									
	Shield type Cylindrical outer ring	Sealed type Cylindrical outer ring		d	D	B	C						
12.700 (.50)	CRY 30 VR		363	12.700	47.625	26.988	25.400						
				Shaft dia.				Basic dynamic load rating C	Basic static load rating C ₀				
				Push fit		Drive fit		Press fit					
				Min.	Max.	Min.	Max.	Min.	Max.				
				32.7(1.287)	500	12.682	12.692	12.698	12.708	12.708	12.718	35 300	55 600

Remarks: 1. The inner ring has an oil hole.
2. Provided with prepacked grease.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952398891
Inside diameter	12.7 mm
Outside diameter	47.625 mm
Thickness	26.988 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE