


## Yoke type track roller CRY36-VR-IKO - CRY36-VR-IKO

<https://www.123bearing.eu/bearing-housing/roller-bearing/yoke-track-roller/cry36-vr-iko>

**IKO**  
**ROLLER FOLLOWERS**  
Non-separable Roller Followers, Inch Series **Full Complement Type/With Inner Ring**



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions: mm(inch)									
	Shield type Cylindrical outer ring	Sealed type Cylindrical outer ring		d	D	B	C						
15.875 (5/8)	<b>CRY 36 VR</b>		599	15.875 (5/8)	57.150 (2 1/4)	33.338(1.3125)	31.750 (1 1/4)						
				Shaft dia.				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>				
				Push fit		Drive fit		Press fit					
				Min.	Max.	Min.	Max.	Min.	Max.				
				38.0(1.417)	600(24)	15.857	15.867	15.873	15.883	15.883	15.893	45 700	80 600

Remarks: 1. The inner ring has an oil hole.  
2. Provided with prepacked grease.

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952398938
Inside diameter	15.875 mm
Outside diameter	57.15 mm
Thickness	33.338 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE