

Yoke type track roller CRY48-VUUR-IKO - CRY48-VUUR-IKO

<https://www.123bearing.eu/bearing-housing/roller-bearing/yoke-track-roller/cry48-vuur-iko>

IKO
ROLLER FOLLOWERS
Non-separable Roller Followers, Inch Series **Full Complement Type/With Inner Ring**

| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions: mm(inch) | | | | | |
|----------------------------|---------------------------------------|---------------------------------------|---------------------|-------------------------------|--------|----------------|--------------|---|--|
| | Shield type Cylindrical outer ring | Sealed type Cylindrical outer ring | | d | D | B | C | | |
| 25.400 (1) | | CRY 48 VUUR | 1 410 | 25.400 | 76.200 | 46.038(1.8125) | 44.450(1.75) | | |
| | | | | Shaft dia. | | | | Basic dynamic load rating C _d N | Basic static load rating C ₀ N |
| d | f | | | Push fit | | Drive fit | | | |
| | | Min. | Max. | Min. | Max. | Min. | Max. | | |
| 54.02(2.125) | 760(30) | 25.377 | 25.390 | 25.397 | 25.410 | 25.408 | 25.420 | 77 600 | 172 000 |

Remarks: 1. The inner ring has an oil hole.
2. Provided with prepacked grease.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952399003 |
| Inside diameter | 25.4 mm |
| Outside diameter | 76.2 mm |
| Thickness | 46.038 mm |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE