

Tapered roller bearing 30228-JR-JTEKT - 30228-JR-KOYO

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/30228-jr-koyo>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
140	250	45.75	42	36	420	570	1 500	1 900	30228JR					
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
4FB	49.4	158	163	236	219	237	9	9.5	3	2.5	0.44	1.38	0.76	8.97

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952419763
Inside diameter	140 mm
Outside diameter	250 mm
Thickness	45.75 mm
Weight	8989 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE