

Tapered roller bearing 28158-28300-JTEKT - 28158-28300-KOYO

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/28158-28300-koyo>

Single-row tapered roller bearings ————— **Koyo**
inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁ max.	r ₁ min.	C _r	C ₁₀	Grease lub.	Oil lub.
40.000	76.200	20.638	20.940	19.607	1.6	1.2	57.3	65.9	5 300	7 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
28158	28300	16.5	47.5	45.0	68.0	71.0	1.6	1.2	0.40	1.49	0.82	0.266	0.137

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250107252
Inside diameter	40 mm
Outside diameter	76.2 mm
Thickness	20.638 mm
Weight	412 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE