


Tapered roller bearing 3780-3730-JTEKT - 3780-3730-KOYO

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/3780-3730-koyo>

Single-row tapered roller bearings inch series **Koyo**



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r_a</i> <small>max.</small>	<i>r_b</i> <small>max.</small>	<i>C_r</i>	<i>C_{0r}</i>	Grease lub.	Oil lub.
50.800	93.264	30.162	30.302	22.812	3.6	0.8	103	137	4 200	5 500

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d_a</i>	<i>d_b</i>	<i>D_a</i>	<i>D_b</i>	<i>r_a</i> <small>max.</small>	<i>r_b</i> <small>max.</small>	<i>e</i>	<i>Y₁</i>	<i>Y₂</i>	Inner ring	Outer ring
3780	3730	22.2	64.0	58.0	84.0	88.0	3.6	0.8	0.34	1.77	0.97	0.547	0.293

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427706
Inside diameter	50.8 mm
Inside diameter	2" inch
Outside diameter	93.264 mm
Outside diameter	3.672" inch
Thickness	30.302 mm
Thickness	1.193" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE