


Tapered roller bearing 39590-39521-JTEKT - 39590-39521-KOYO

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/39590-39521-koyo>

Single-row tapered roller bearings inch series **Koyo**



Boundary dimensions (mm)								Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r_a</i>	<i>r_b</i>	<i>r₁</i>	<i>C_r</i>	<i>C₁₀</i>	Grease lub.	Oil lub.
66.675	112.712	30.162	30.162	22.812	3.6	0.8		147	207	3 300	4 500

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d_a</i>	<i>d_b</i>	<i>D_a</i>	<i>D_b</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>e</i>	<i>Y₁</i>	<i>Y₂</i>	Inner ring	Outer ring
39590	39521	23.3	80.0	74.0	103.0	107.0	3.6	0.8	0.34	1.77	0.97	0.832	0.360

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428611
Inside diameter	66.675 mm
Outside diameter	112.712 mm
Thickness	30.162 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE