

## Tapered roller bearing 29688-29620-JTEKT - 29688-29620-KOYO

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/29688-29620-koyo>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_a$ max.	$r_1$ max.	$C_r$	$C_{10}$	Grease lub.	Oil lub.
73.817	112.712	25.400	25.400	19.050	1.6	3.2	97.0	155	3 200	4 300

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	$a$	$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.	$e$	$Y_1$	$Y_2$	Inner ring	Outer ring
29688	29620	26.2	83.0	81.0	101.0	109.0	1.6	3.2	0.49	1.23	0.68	0.588	0.270

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429007
Inside diameter	73.817 mm
Outside diameter	112.712 mm
Thickness	25.4 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE