

Tapered roller bearing 98335-98788-JTEKT - 98335-98788-KOYO

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/98335-98788-koyo>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁ max.	r ₁ min.	C _r	C ₁₀	Grease lub.	Oil lub.
85.000	200.000	52.761	49.212	34.925	3.6	3.2	347	471	1 400	1 900

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
98335	98788	54.5	115.0	109.0	174.0	188.0	3.6	3.2	0.83	0.95	0.52	5.47	2.28

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429489
Inside diameter	85 mm
Outside diameter	200 mm
Thickness	52.761 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE