

Tapered roller bearing 594A-592XE-JTEKT - 594A-592XE-KOYO

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/594a-592xe-koyo>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|---------|--------|--------|--------|----------------|----------------|----------------|-------------------------|-----------------|--------------------------------------|----------|
| d | D | T | B | C | d _a | d _b | r _a | C _r | C ₁₀ | Grease lub. | Oil lub. |
| 95.250 | 147.638 | 35.717 | 36.322 | 26.192 | 5.2 | 0.8 | | 183 | 287 | 2 400 | 3 300 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | (Refer.) Mass (kg) | |
|-------------|------------|------------------|--------------------------|----------------|----------------|----------------|---------------------|---------------------|----------|--------------------|----------------|--------------------|------------|
| Inner ring | Outer ring | a | d _a | d _b | D _a | D _b | r _a max. | r _b max. | e | Y ₁ | Y ₂ | Inner ring | Outer ring |
| 594A | 592XE | 33.4 | 113.0 | 104.0 | 135.0 | 142.0 | 5.2 | 0.8 | 0.44 | 1.36 | 0.75 | 1.45 | 0.620 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952429823 |
| Inside diameter | 95.25 mm |
| Outside diameter | 147.638 mm |
| Thickness | 35.717 mm |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE