

Tapered roller bearing HH221442-HH221410-JTEKT - HH221442-HH221410-KOYO

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/hh221442-hh221410-koyo>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	C _r	C ₁₀	Grease lub. Oil lub.		
98.425	190.500	57.150	57.531	46.038	3.6	3.2	440	602	2 000	2 700	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
HH221442	HH221410	42.5	119.0	113.0	171.0	179.0	3.6	3.2	0.33	1.79	0.99	4.97	2.21

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429885
Inside diameter	98.425 mm
Outside diameter	190.5 mm
Thickness	57.15 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE