

Tapered roller bearing

L555249-L555210-JTEKT - L555249-L555210-KOYO

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/l555249-l555210-koyo>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|---------|--------|--------|--------|---------------|---------------|-------------------------|----------|--------------------------------------|----------|
| d | D | T | B | C | r_1 max. | r_1 min. | C_r | C_{10} | Grease lub. | Oil lub. |
| 292.100 | 374.850 | 47.625 | 47.625 | 34.825 | 3.6 | 3.2 | 488 | 971 | 760 | 1 000 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | Constant | Axial load factors | | (Refer.) Mass (kg) | | |
|-------------|------------|------------------|--------------------------|-------|-------|-------|---------------|---------------|--------------------|-------|--------------------|------------|------------|
| Inner ring | Outer ring | a | d_a | d_b | D_a | D_b | r_a max. | r_b max. | e | Y_1 | Y_2 | Inner ring | Outer ring |
| L555249 | L555210 | 64.7 | 306.0 | 309.0 | 351.0 | 360.0 | 3.6 | 3.2 | 0.40 | 1.49 | 0.82 | 7.97 | 3.53 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952431888 |
| Inside diameter | 292.1 mm |
| Outside diameter | 374.65 mm |
| Thickness | 47.625 mm |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE