


## Cam follower CF12-FBR-IKO - CF12-FBR-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cf12-fbr-iko>

IKO

### CAM FOLLOWERS

Stainless Steel Made Cam Followers With Cage/With Hexagon Hole



Stud dia. mm	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G	G <sub>1</sub>
	Shield type		Sealed type							
	With crowned outer ring	With cylindrical outer ring	With ribbed outer ring	With cylindrical outer ring						
12	CF 12 FBR				95	30	14	12	M12×1.5	13

Boundary dimensions mm								Mounting dimension f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N
B	B <sub>1</sub>	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>	H					
15.2 max	40.2 max	25	6	0.6	6	3	6	—	21	21.9	6 330	7 830

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952440026
Inside diameter	12 mm
Outside diameter	30 mm
Thickness	14 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE