


Cam follower CF8-VUUM-IKO - CF8-VUUM-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cf8-vuum-iko>

IKO

CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Screwdriver Slot



CF-VUU													
Stud dia. mm	Identification number								Mass (Ref.)				
	Shield type				Sealed type				$\bar{m}$	D	C	d_1	
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring									
8	CF 8 VUUM								29	19	11	8	
Boundary dimensions mm													
G	G_1	B max	B_1 max	B_2	B_3	C_1	G_2	f mm	Mounting dimension Min. mm	Maximum tightening torque N·m	Basic dynamic load rating kg	Basic static load rating kg	Maximum allowable static load N
M 8×1	10	12.2	32.2	20	—	0.6	*4	— 0.3	13	7.1	8 170	11 200	4 620

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952440224
Inside diameter	8 mm
Outside diameter	19 mm
Thickness	11 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE