


Cam follower CF10-VM-IKO - CF10-VM-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cf10-vm-iko>



CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm	Identification number								CF-V					
	Shield type				Sealed type				Mass (Ref.)					
	With crowned outer ring		With cylindrical outer ring		With crowned outer ring		With cylindrical outer ring		g	D	C	d ₁		
10	CF 10		VM						46	22	12	10		
Boundary dimensions mm														
G	G ₁	B _{max}	B _{1 max}	B ₂	B ₃	C ₁	g ₁	g ₂	f _{max} (°)	f _{min}	Maximum tightening torque N·m	Static load rating N	Dynamic load rating C ₀	Maximum allowable static load N
M10×1	12	13.2	36.2	23	—	0.6	*4	—	0.3	16	14.7	9 570	14 500	8 650

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952440262
Inside diameter	10 mm
Outside diameter	22 mm
Thickness	12 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE