


Cam follower CF20-1-VUU-IKO - CF20-1-VUU-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cf20-1-vuu-iko>



CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Screwdriver Slot



| Stud dia. mm | Identification number | | | | | | | | Mass (Ref.) g | D | C | d ₁ | | |
|------------------------|-------------------------|----------|-----------------------------|----------------|-------------------------|----------------|-----------------------------|----------------|------------------------|--|--|--|--|--|
| | Shield type | | | | Sealed type | | | | | | | | | |
| | With crowned outer ring | | With cylindrical outer ring | | With crowned outer ring | | With cylindrical outer ring | | | | | | | |
| 20 | | | | | | | CF 20-1 VUU | | 390 | 47 | 24 | 20 | | |
| Boundary dimensions mm | | | | | | | | | | | | | | |
| G | G ₁ | B max | B ₁ max | B ₂ | B ₃ | C ₁ | g ₁ | g ₂ | f ⁽¹⁾ mm | Mounting dimension f Min. mm | Maximum tightening torque N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N | Maximum allowable static load N |
| M20 × 1.5 | 21 | 25.6 | 66.1 | 40.5 | 9 | 0.8 | 8 | 4 | 1 | 34 | 119 | 33 200 | 64 500 | 37 500 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952440620 |
| Inside diameter | 20 mm |
| Outside diameter | 47 mm |
| Thickness | 24 mm |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE