


Cam follower CF30-V-IKO - CF30-V-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cf30-v-iko>



CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm	Identification number								CF-V					
	Shield type				Sealed type				Mass (Ref.) g	D	C	d ₁		
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring						
30	CF30 V								1 870	80	35	30		
Boundary dimensions mm														
G	G ₁	B max	B ₁ max	B ₂	B ₃	C ₁	g ₁	g ₂	f _{max} (°)	f Min. mm	Mounting torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
M30 × 1.5	32	37	100	63	15	1	8	4	1	49	438	67 700	144 000	85 900

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952440729
Inside diameter	30 mm
Outside diameter	80 mm
Thickness	35 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE