


Cam follower CF30-VUUR-IKO - CF30-VUUR-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cf30-vuur-iko>



CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Screwdriver Slot



CF-VUUR

Stud dia. mm	Identification number								Mass (Ref.) g	D	C	d ₁
	Shield type				Sealed type							
	With crowned outer ring		With cylindrical outer ring		With crowned outer ring		With cylindrical outer ring					
30					CF 30		VUUR		1 870	80	35	30

Boundary dimensions mm														
G	G ₁	B _{max}	B _{1 max}	B ₂	B ₃	C ₁	g ₁	g ₂	f ⁽¹⁾ mm	Mounting diameter f _{min} mm	Maximum tightening torque C N·m	Basic static load rating C ₀ N	Maximum allowable static load N	
M30 × 1.5	32	37	100	63	15	1	8	4	1	49	438	67 700	144 000	85 900

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952440736
Inside diameter	30 mm
Outside diameter	80 mm
Thickness	35 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE