


Cam follower CF12-UU-IKO - CF12-UU-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cf12-uu-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF-UU

| Stud dia. mm | Identification number | | | | Max (Ref.) g | D | C | d ₁ | G |
|-----------------|----------------------------|--------------------------------|----------------------------|--------------------------------|--------------------|----|----|----------------|---------|
| | Shield type | | Sealed type | | | | | | |
| | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | | | | | |
| 12 | | | | CF 12 UU | 95 | 30 | 14 | 12 | M12×1.5 |

| Boundary dimensions mm | | | | | | | | | | Mounting torque N·m | Ball dynamic load rating C | Ball static load rating C ₀ | Maximum allowable static load N |
|------------------------|---------|----------------|----------------|----------------|----------------|----------------|----------------|---------------------------|-----------------|---------------------------|----------------------------------|--|--|
| G ₁ | B | B ₁ | B ₂ | B ₃ | C ₁ | g ₁ | g ₂ | r _s max (°) | f Min. mm | | | | |
| 13 | 15.2max | 40.2max | 25 | 6 | 0.6 | 6 | 3 | 0.6 | 21 | 21.9 | 7 910 | 9 790 | 9 790 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952441276 |
| Inside diameter | 12 mm |
| Outside diameter | 30 mm |
| Thickness | 14 mm |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE