

Cam follower CF18-UUR-IKO - CF18-UUR-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cf18-uur-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm	Identification number				Max. (Ref.)				
	Shield type		Sealed type		g	D	C	d ₁	G
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
18	CF 18 UUR				250	40	20	18	M18×1.5

Boundary dimensions mm											Mounting diameter f Min. mm	Maximum lighting torque N·m	Ball diameter load rating C	Ball static load rating C ₀	Maximum allowable static load N
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _s max	(°)	r _s					
19	21.6max	58.1max	36.5	8	0.8	6	3	1	29	86.2	14 800	25 200	25 200		

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441382
Inside diameter	18 mm
Inside diameter	0.709" inch
Outside diameter	40 mm
Outside diameter	1.575" inch
Thickness	20 mm
Thickness	0.787" inch
Weight	250 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE