


Cam follower CF30-IKO - CF30-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cf30-iko>

IKO

CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF

Stud dia. mm	Identification number				Mass (Ref.)				
	Shield type		Sealed type		g	D	C	d ₁	G
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
30	CF 30				1 870	80	35	30	M30 × 1.5

Boundary dimensions mm															
G ₁	B	B ₁	B ₂	B ₃	C ₁	G ₂	f _{max} (°)	f _{min} mm	Maximum bearing torque N·m	Basic dynamic load rating C ₀	Basic static load rating C ₀	Basic dynamic static load N			
32	37	max	100	max	63	15	1	8	4	1	49	438	45 400	85 100	85 100

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441573
Inside diameter	30 mm
Outside diameter	80 mm
Thickness	35 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE