


## Cam follower CF30-UU-IKO - CF30-UU-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cf30-uu-iko>



### CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF-UU

Stud dia. mm	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G
	Shield type		Sealed type						
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
30				<b>CF 30 UU</b>	1 870	80	35	30	M30×1.5

Boundary dimensions mm										Boreing dimension f Min. mm	Maximum bearing torque N·m	Ball dynamic load rating C N	Ball static load rating C <sub>0</sub> N	Maximum allowable static load N	
G <sub>1</sub>	B	B <sub>1</sub>	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>	r <sub>max</sub> <sup>(*)</sup>	r <sub>min</sub>						
32	37	max	100	max	63	15	1	8	4	1	49	438	45 400	85 100	85 100

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441597
Inside diameter	30 mm
Inside diameter	1.181" inch
Outside diameter	80 mm
Outside diameter	3.15" inch
Thickness	35 mm
Thickness	1.378" inch
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE