


## Cam follower CF8-VBM-IKO - CF8-VBM-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cf8-vbm-iko>



### CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Hexagon Hole



CF-VB

Stud dia. mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			g	D	C	d <sub>1</sub>
	With crowned outer ring	With cylindrical outer ring		With crowned outer ring	With cylindrical outer ring					
8		CF 8	VBM				29	19	11	8

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N	
G	G <sub>1</sub>	B max	B <sub>1</sub> max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	B <sub>2</sub>	H K/min						
M 8×1	10	12.2	32.2	20	—	0.6	—	—	4	0.3	13	7.1	8 170	11 200	4 620

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441795
Inside diameter	8 mm
Inside diameter	0.315" inch
Outside diameter	19 mm
Outside diameter	0.748" inch
Thickness	11 mm
Thickness	0.433" inch
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE