


Cam follower CF10-VB-IKO - CF10-VB-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cf10-vb-iko>



CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Hexagon Hole



CF--VB

Stud dia. mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			g	D	C	d ₁
	With crowned outer ring	With cylindrical outer ring		With crowned outer ring	With cylindrical outer ring					
10		CF 10 VB				46	22	12	10	

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
G	G ₁	B max	B ₁ max	B ₂	B ₃	C ₁	g ₁	B ₂	H ^(*) K/min						
M10×1.25	12	13.2	36.2	23	—	0.6	—	—	4	0.3	16	13.8	9 570	14 500	8 650

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441832
Inside diameter	10 mm
Outside diameter	22 mm
Thickness	12 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE