

Cam follower CF8-BUURM-IKO - CF8-BUURM-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cf8-buurm-iko>

IKO

CAM FOLLOWERS

Standard Type Cam Followers **With Cage/With Hexagon Hole**

CF--BUUR

Stud dia. mm	Identification number				Mass (Ref.) g	D	C	d ₁	G					
	Shield type		Sealed type											
8	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring	28.5	19	11	8	M 8×1					
Boundary dimensions mm					Mounting dimension f Min. mm	Maximum spinning torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N					
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	H	r _s μm	f	T _{max}	C	C ₀	N _{max}
10	12.2max	32.2max	20	—	0.6	—	—	4	0.3	13	7.1	4 250	4 740	4 620

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952442648
Inside diameter	8 mm
Outside diameter	19 mm
Thickness	11 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE