


Cam follower CFES18-BUUR-IKO - CFES18-BUUR-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cfes18-buur-iko>



CAM FOLLOWERS

Solid Eccentric Stud Type Cam Followers | With Cage/With Hexagon Hole



CFES-BUUR

Stud dia. mm	Identification number								Mass (Ref.) g	D	C	d ₁				
	Shield type				Sealed type											
18	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	250	40	20	18				
	CFES 18				BUUR											
Boundary dimensions mm																
G	G ₁	B max	B ₁ max	B ₂	B ₃	C ₁	g ₁	g ₂	H K _{max} (°)	Eccentricity E	Mounting dimension f Min. mm	Maximum spinning torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
M18×1.5	19	21.6	58.1	36.5	8	0.8	6	3	8	1	0.6	29	86.2	14 800	25 200	25 200

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952443676
Inside diameter	18 mm
Outside diameter	40 mm
Thickness	20 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE