

## Cam follower CFE12-1-B-IKO - CFE12-1-B-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cfe12-1-b-iko>

IKO

### CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Hexagon Hole



CFE-B

| Outside diameter of eccentric roller mm | Identification number   |                             |                         |                             | Mass (Ref.) |    |    |                |
|---|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------|----|----|----------------|
|   | Shield type             |                             | Sealed type             |                             | Ø           | D  | C  | d <sub>e</sub> |
|   | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring |             |    |    |                |
| 16                                      | CFE 12-1 B              |                             |                         |                             | 115         | 32 | 14 | 16             |

| Boundary dimensions mm |                |                  |                    |                |                |                |      |                  |                  | Mounting dimension f Min. mm | Maximum splining torque N·m | Basic dynamic load rating C N | Basic static load rating C <sub>0</sub> N | Maximum allowable static load N |       |
|------------------------|----------------|------------------|--------------------|----------------|----------------|----------------|------|------------------|------------------|------------------------------|-----------------------------|-------------------------------|---|---------------------------------|-------|
| G                      | B <sub>3</sub> | B <sub>max</sub> | B <sub>1 max</sub> | B <sub>2</sub> | C <sub>1</sub> | G <sub>1</sub> | H    | H <sub>max</sub> | H <sub>min</sub> |                              |                             |                               |   |                                 |       |
| M12×1.5                | 11.5           | 15.2             | 40.2               | 25             | 0.6            | 6              | 13.5 | 6                | 0,6              | 0,8                          | 21                          | 21,9                          | 7 910                                     | 9 790                           | 9 790 |

## PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | IKO           |
| N° Ean13         | 3616060459466 |
| Inside diameter  | 16 mm         |
| Outside diameter | 32 mm         |
| Thickness        | 14 mm         |
| Packaging        | 1             |

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE