

## Cam follower CFE24-1-B-IKO - CFE24-1-B-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cfe24-1-b-iko>

IKO

### CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Hexagon Hole



CFE-B

Outside diameter of eccentric collar mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		Ø	D	C	d <sub>e</sub>
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
33	CFE 24-1 B				1 220	72	29	33

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum splining torque N-m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N	
G	B <sub>3</sub>	B <sub>max</sub>	B <sub>1 max</sub>	B <sub>2</sub>	C <sub>1</sub>	G <sub>1</sub>	H	(1) f <sub>max</sub>	ε						
M24×1.5	25.5	30.6	80.1	49.5	0.8	8	24	12	1	0.8	40	215	30 500	52 600	52 000

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060459589
Inside diameter	33 mm
Outside diameter	72 mm
Thickness	29 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE