


Cam follower CFE30-1-B-IKO - CFE30-1-B-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cfe30-1-b-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers | With Cage | With Hexagon Hole



CFE-B

Outside diameter of outer ring mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
41	CFE 30-1 B				2 190	85	35	41

Boundary dimensions mm										Mounting dimension f mm	Maximum splining torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
G	B ₃	B _{max}	B _{1 max}	B ₂	C ₁	G ₁	H	(1) E	ε						
M30×1.5	32.5	37	100	63	1	8	30.5	17	1	1.5	49	438	45 400	85 100	85 100

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060459657
Inside diameter	41 mm
Inside diameter	1.614" inch
Outside diameter	85 mm
Outside diameter	3.346" inch
Thickness	35 mm
Thickness	1.378" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE