


## Cam follower CFE10-IKO - CFE10-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cfe10-iko>

IKO

### CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			ø	D	C	d <sub>2</sub>
	With crowned outer ring	With cylindrical outer ring	CFE 10	With crowned outer ring	With cylindrical outer ring					
13			CFE 10				49.5	22	12	13

Boundary dimensions mm										Essentiality g	Mounting dimension f mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N
G	B <sub>3</sub>	B max	B <sub>1</sub> max	B <sub>2</sub>	C <sub>1</sub>	G <sub>1</sub>	r <sub>max</sub> (°)	g	e						
M10×1.25	10.5	13.2	36.2	23	0.6	*4	12.5	0.3	0.4	16	13.8	5 430	6 890	6 890	

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060459817
Inside diameter	13 mm
Inside diameter	0.512" inch
Outside diameter	22 mm
Outside diameter	0.866" inch
Thickness	12 mm
Thickness	0.472" inch
Weight	49.5 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE