


Cam follower CFE16-IKO - CFE16-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cfe16-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number					Mass (Ref.)			
	Shield type		Sealed type			Ø	D	C	d ₂
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
22	CFE 16					190	35	18	22

Boundary dimensions mm										Essentiality g	Mounting dimension f mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
G	B ₃	B max	B ₁ max	B ₂	C ₁	G ₁	G ₁ fits	(1)	e						
M16×1.5	15.5	19.6	52.1	32.5	0.8	6	17	0.6	0.8	26	58.5	12 000	18 300	18 300	

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060459978
Inside diameter	22 mm
Outside diameter	35 mm
Thickness	18 mm
Weight	190 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE