


## Cam follower CFE18-UUR-IKO - CFE18-UUR-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cfe18-uur-iko>

**IKO**  
**CAM FOLLOWERS**  
Eccentric Type Cam Followers **With Cage/With Screwdriver Slot**



Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		$\emptyset$	D	C	$d_2$
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
<b>24</b>			<b>CFE 18 UUR</b>		280	40	20	24

Boundary dimensions mm										Eccentricity $e$	Mounting dimension $f$ Min. mm	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating $C_0$ N	Maximum allowable static load N
G	$B_3$	$B$ max	$B_1$ max	$B_2$	$C_1$	$G_1$	$r_{max}$	$r_{min}$	$r$						
M18x1.5	17.5	21.6	58.1	36.5	0.8	6	19	1	0.8	29	86.2	14 800	25 200	25 200	

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460011
Inside diameter	24 mm
Outside diameter	40 mm
Thickness	20 mm
Weight	280 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE