

## Cam follower CFE12-VB-IKO - CFE12-VB-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cfe12-vb-iko>

IKO

### CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole



Outside diameter of eccentric collar mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			Ø	D	C	d <sub>e</sub>
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring						
16	CFE 12 VB						107	30	14	16

  

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum splining torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N	
G	B <sub>3</sub>	B <sub>1</sub> max	B <sub>2</sub> max	C <sub>1</sub>	G <sub>1</sub>	H	ε	Excentricity e	Flange						
M12×1.5	11.5	15.2	40.2	25	0.6	6	13.5	6	0.6	0.8	21	21.9	13 500	19 700	13 200

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460462
Inside diameter	16 mm
Outside diameter	30 mm
Thickness	14 mm
Weight	107 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE