


## Cam follower CFE30-VBUU-IKO - CFE30-VBUU-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cfe30-vbuu-iko>

IKO

**CAM FOLLOWERS**

Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole



CFE-VBUU

Outside diameter of eccentric roller mm	Identification number								Mass (Ref.)			
	Shield type				Sealed type				Ø	D	C	d <sub>e</sub>
	With crowned outer ring		With cylindrical outer ring		With crowned outer ring		With cylindrical outer ring					
<b>41</b>					<b>CFE 30 VBUU</b>				2 030	80	35	41

Boundary dimensions mm											Mounting dimension f Min. mm	Maximum splining torque Ni-m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum ultimate static load N
G	B <sub>3</sub>	B <sub>1</sub> max	B <sub>2</sub> max	C <sub>1</sub>	G <sub>1</sub>	H	(*)	Excentricity e	Flange diameter	Flange thickness					
M30×1.5	32.5	37	100	63	1	8	30.5	17	1	1.5	49	438	67 700	144 000	85 900

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460790
Inside diameter	41 mm
Outside diameter	80 mm
Thickness	35 mm
Weight	2030 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE