


## Cam follower CFE6-VUUR-IKO - CFE6-VUUR-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cfe6-vuur-iko>

IKO

### CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot



Outside diameter of eccentric outer ring mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d <sub>e</sub>
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
9	CFE 6 VUUR				21	16	11	9

Boundary dimensions mm														
G	B <sub>3</sub>	B <sub>max</sub>	B <sub>2</sub> max	B <sub>2</sub>	C <sub>1</sub>	β <sub>1</sub>	G <sub>1</sub>	r <sub>1</sub> min	Eccentricity E	Mounting dimension f Min. mm	Maximum ignoring torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N
M 6 × 1	7.5	12.2	28.2	16	0.6	*4	8.5	0.3	0.4	11	2.7	6 980	8 500	1 950

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460875
Inside diameter	9 mm
Outside diameter	16 mm
Thickness	11 mm
Weight	21 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE