


## Cam follower CFE10-VUU-IKO - CFE10-VUU-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cfe10-vuu-iko>

**IKO**  
**CAM FOLLOWERS**  
Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot



Outside diameter of eccentric collar mm	Identification number				Mass (Ref.)									
	Shield type		Sealed type		g	D	C	d <sub>e</sub>						
13	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	50.5	22	12	13						
CFE 10 VUU														
Boundary dimensions mm														
G	B <sub>3</sub>	B <sub>max</sub>	B <sub>1</sub> max	B <sub>2</sub>	C <sub>1</sub>	g <sub>1</sub>	G <sub>1</sub>	r <sub>1</sub> min	Excentricity E	Mounting dimension f Min. mm	Maximum operating torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N
M10 × 1.25	10.5	13.2	36.2	23	0.6	*4	12.5	0.3	0.4	16	13.8	9 570	14 500	8 650

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460967
Inside diameter	13 mm
Inside diameter	0.512" inch
Outside diameter	22 mm
Outside diameter	0.866" inch
Thickness	12 mm
Thickness	0.472" inch
Weight	50.5 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE