

Cam follower CFE12-VR-IKO - CFE12-VR-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cfe12-vr-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot

Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d ₀
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
16	CFE 12	VR			107	30	14	16

Boundary dimensions mm										
G	B ₃	B _{max}	B _{1max}	B ₂	C ₁	B ₁	G ₁	r _{1min}	E	f
M12 × 1.5	11.5	15.2	40.2	25	0.6	6	13.5	0.6	0.8	21

Mounting dimension	Maximum operating torque	Basic dynamic load rating	Basic static load rating	Maximum allowable static load
f Min. mm	N·m	C N	C ₀ N	N
21	21.9	13 500	19 700	13 200

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060461018
Inside diameter	16 mm
Outside diameter	30 mm
Thickness	14 mm
Weight	107 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE