

Cam follower CFE16-VUUR-IKO - CFE16-VUUR-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cfe16-vuur-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers **Full Complement Type/With Screwdriver Slot**



CFE -- VUUR

Outside diameter of eccentric roller mm	Identification number				Mass (Ref.) g	D	C	d _a
	Shield type		Sealed type					
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
22			CFE 16	VUUR	193	35	18	22

Boundary dimensions mm										Mounting dimension f mm	Maximum aligning torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
G	B ₃	B _{max}	B ₁ max	B ₂	C ₁	g ₁	G ₁	r ₁ max	E					
M16 × 1.5	15.5	19.6	52.1	32.5	0.8	6	17	0.6	0.8	26	58.5	20 700	37 600	23 200

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060461117
Inside diameter	22 mm
Outside diameter	35 mm
Thickness	18 mm
Weight	193 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE