


Cam follower CFE30-V-IKO - CFE30-V-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cfe30-v-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)		
	Shield type		Sealed type		g	D	C
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring			
41		CFE 30 V			2 030	80	35

Boundary dimensions mm									
G	B ₃	B ₂ max	B ₁ max	B ₂	C ₁	g ₁	G ₁	r ₁ min	E
M30 × 1.5	32.5	37	100	63	1	8	30.5	1	1.5

Mounting dimension f mm	Maximum aligning torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
49	438	67 700	144 000	85 900

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060461315
Inside diameter	41 mm
Inside diameter	1.614" inch
Outside diameter	80 mm
Outside diameter	3.15" inch
Thickness	35 mm
Thickness	1.378" inch
Weight	2030 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE