


Cam follower CF-RU1-6-IKO - CF-RU1-6-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cf-ru1-6-iko>

IKO

CAM FOLLOWERS

Centralized Lubrication Type Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	With crowned outer ring	With cylindrical outer ring		D	C	d ₁	G	G ₁
6	CF-RU1- 6		18.5	16	11	6	M 6 x 1	8

B _{max}	B _{1max}	B ₂	B ₃	C ₁	G ₂	M ₁	M ₂	r _s min	Mounting dimension f ₁ mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
12.2	28.2	16	—	0.6	—	M6x 0.75		0.3	11	2.7	3 660	3 650	1 950

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060461520
Inside diameter	6 mm
Outside diameter	16 mm
Thickness	11 mm
Weight	18.5 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE