


Cam follower CR22-BUUR-IKO - CR22-BUUR-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cr22-buur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Hexagon Hole



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type		Sealed type								
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring							
12.700 ($\frac{1}{2}$)	CR 22 BUUR				157	34.925 ($\frac{1}{2}$)	19.050 ($\frac{3}{4}$)	12.700 ($\frac{1}{2}$)	J ₁ -20	15.875 ($\frac{1}{2}$)	
Boundary dimensions mm/inch											
B max	B ₂	B ₃	C ₁	E ₁	E ₂	H	r	Bearing dimension f Mm (mm/inch)	Maximum tightening torque C N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
20.4 (0.80)	21.750 ($\frac{1}{2}$)	7.538 ($\frac{3}{4}$)	0.794 ($\frac{1}{4}$)	4.762 ($\frac{1}{2}$)	3.175 ($\frac{1}{4}$)	6.350 ($\frac{1}{4}$)	1.588 ($\frac{1}{4}$)	21.828 ($\frac{3}{4}$)	27.7	14 200	16 000

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060462589
Inside diameter	12.7 mm
Outside diameter	34.925 mm
Thickness	19.05 mm
Weight	157 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE