


Cam follower CR12-R-IKO - CR12-R-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cr12-r-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type With covered outer ring	Shield type With cylindrical outer ring	Sealed type With covered outer ring	Sealed type With cylindrical outer ring						
9.525 ($\frac{3}{8}$)	CR 12 R				35	19.050 $\frac{3}{4}$	12.700 $\frac{1}{2}$	9.525 $\frac{3}{8}$	7/16-24	9.525 $\frac{3}{8}$
Boundary dimensions mm(inch)						Mounting dimension f Min. mm(inch)	Maximum tightening torque C N·m	Basic dynamic load rating C ₀ N	Basic static load rating C ₀ N	
B max	B ₂	B ₃	C ₁	S ₁	S ₂					r
14.2 0.56	22.225 $\frac{7}{8}$	6.350 $\frac{1}{4}$	0.794 $\frac{1}{16}$	4.762 $\frac{3}{16}$	2.381 $\frac{3}{32}$	0.794 $\frac{1}{16}$	13.464 $\frac{1}{2}$	10.8	4 420	5 110

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060462848
Inside diameter	9.525 mm
Outside diameter	19.05 mm
Thickness	12.7 mm
Weight	35 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE