


Cam follower CR16-IKO - CR16-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cr16-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				g	D	C	d ₁	G UNF	G ₁
	Shield type		Sealed type							
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring						
11.112 ($\frac{7}{16}$)	CR 16				73	25.400	15.875	11.112	$\frac{1}{8}$ -20	12.700
Boundary dimensions mm(inch)										
B max	B ₂	B ₃	C ₁	S ₁	S ₂	r	Bearing dimension f Min. mm(inch)	Maximum tightening torque C	Basic dynamic load rating C ₀	Basic static load rating C ₀
17.3 0.68	25.400	6.350	0.794	4.762	3.175	1.911	17.859	17.4	8 910	10 800

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060462916
Inside diameter	11.112 mm
Outside diameter	25.4 mm
Thickness	15.875 mm
Weight	73 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE