

Cam follower CR36-UUR-IKO - CR36-UUR-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cr36-uur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type With covered outer ring	Shield type With cylindrical outer ring	Sealed type With covered outer ring	Sealed type With cylindrical outer ring						
22.225 ($\frac{7}{8}$)			CR 36	UUR	750	57.150 ($2\frac{1}{4}$)	21.750 ($1\frac{1}{4}$)	22.225 ($\frac{7}{8}$)	7-14	25.400 (1)
Boundary dimensions mm(inch)										
B max	B ₂	B ₃	C ₁	S ₁	S ₂	r	Bearing dimension f Min. mm(inch)	Maximum tightening torque C	Basic dynamic load rating C ₀	Basic static load rating C ₀
33.5 (1.32)	50.800 (2)	12.700 ($\frac{1}{2}$)	0.794 ($\frac{1}{8}$)	4.762 ($\frac{3}{8}$)	4.762 ($\frac{3}{8}$)	1.588 ($\frac{1}{8}$)	37.306 (1.5)	192	32 500	69 900

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463050
Inside diameter	22.225 mm
Outside diameter	57.15 mm
Thickness	31.75 mm
Weight	750 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE