

Cam follower CR12-V-IKO - CR12-V-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cr12-v-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



| Stud dia. mm (inch) | Identification number | | | | Mass (Ref.) g | D | C | d ₁ | G | G ₁ |
|------------------------------|---|---|---|---|--|--|--|--|----------------|----------------|
| | Shield type With covered outer ring | Shield type With cylindrical outer ring | Spigot type With splined outer ring | Spigot type With cylindrical outer ring | | | | | | |
| 9.525 (3/8) | | CR 12 V | | | 36 | 19.050 | 12.700 | 9.525 | 1/2-24 | 9.525 |
| Boundary dimensions mm(inch) | | | | | Mounting dimension f Min. mm(inch) | Maximum tightening torque N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N | | |
| B max | B ₂ | B ₃ | C ₁ | g ₁ | | | | | g ₂ | r |
| 14.208 | 22.225 | 8.950 | 0.794 | 4.782 | 2.381 | 0.794 | 13.484 | 10.8 | 8 710 | 12 300 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3616060463401 |
| Inside diameter | 9.525 mm |
| Inside diameter | 3/8" inch |
| Outside diameter | 19.05 mm |
| Outside diameter | 3/4" inch |
| Thickness | 12.7 mm |
| Thickness | 1/2" inch |
| Weight | 36 g |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE