


Cam follower CR16-VUU-IKO - CR16-VUU-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cr16-vuu-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



CR-VUU

| Stud dia. mm (inch) | Identification number | | | | Mass (Ref.) | | | | | |
|------------------------------|--|--|---|--|----------------|----|------------|--------------------------|---------------------------|--|
| | Shield type With cover With cylindrical outer ring | | Sleeved type With cylindrical outer ring | | g | D | C | d ₁ | G UNF | G ₁ |
| 11.112 ($\frac{7}{16}$) | | | | | CR 16 VUU | 74 | 25.400 (1) | 15.875 ($\frac{5}{8}$) | 11.112 ($\frac{7}{16}$) | $\frac{3}{8}$ -20 (12.700) ($\frac{1}{2}$) |

| Boundary dimensions mm(inch) | | | | | | | Mounting dimension f Min. mm(inch) | Maximum tightening torque N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N |
|------------------------------|----------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|---|--|--|--|
| B max | B ₂ | B ₃ | C ₁ | g ₁ | g ₂ | r | | | | |
| 17.3 (0.68) | 25.400 (1) | 8.350 ($\frac{1}{2}$) | 0.794 ($\frac{1}{4}$) | 4.762 ($\frac{3}{8}$) | 3.175 ($\frac{1}{8}$) | 1.191 ($\frac{1}{8}$) | 17.658 (3/4) | 17.4 | 13 100 | 22 700 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3616060463579 |
| Inside diameter | 11.112 mm |
| Outside diameter | 25.4 mm |
| Thickness | 15.875 mm |
| Weight | 74 g |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE