

Cam follower CR18-V-IKO - CR18-V-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cr18-v-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Identification number						Mass (Ref.)				
Stud dia. mm (inch)	Shield type		Sleeved type		ϕ	D	C	d_1	G UNF	G_1
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring						
11.112 ($\frac{7}{16}$)		CR 18 V			85	28.575 ($\frac{11}{16}$)	15.875 ($\frac{5}{8}$)	11.112 ($\frac{7}{16}$)	$\frac{5}{16}$ - 20	12.700 ($\frac{1}{2}$)

Boundary dimensions mm (inch)							Mounting dimension f mm (inch)		Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C_0 N
B_{max}	B_2	B_3	C_1	S_1	S_2	r	f Min.				
17.3 (0.68)	25.400 ($\frac{1}{16}$)	8.350 ($\frac{1}{4}$)	6.794 ($\frac{1}{4}$)	4.762 ($\frac{1}{4}$)	3.175 ($\frac{1}{8}$)	1.588 ($\frac{1}{16}$)	19.050 ($\frac{3}{4}$)	17.4	13	100	22 700

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463630
Inside diameter	11.112 mm
Outside diameter	28.575 mm
Thickness	15.875 mm
Weight	85 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE