


Cam follower CR18-VUU-IKO - CR18-VUU-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cr18-vuu-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



CR-VUU

Stud dia. mm (in)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Spigot type With offset outer ring	Spigot type With cylindrical outer ring						
11.112 ($\frac{7}{16}$)				CR 18 VUU	85	28.575 ($\frac{11}{4}$)	15.875 ($\frac{5}{8}$)	11.112 ($\frac{7}{16}$)	$\frac{3}{8}$ -20	12.700 ($\frac{1}{2}$)

Boundary dimensions mm(inch)							Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
B max	B ₂	B ₃	C ₁	g ₁	g ₂	r				
17.3 (0.68)	25.400 (1)	8.350 ($\frac{1}{2}$)	8.794 ($\frac{5}{8}$)	4.762 ($\frac{3}{8}$)	3.175 ($\frac{1}{8}$)	1.588 ($\frac{1}{16}$)	19.660 ($\frac{3}{4}$)	17.4	13 100	22 700

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463654
Inside diameter	11.112 mm
Outside diameter	28.575 mm
Thickness	15.875 mm
Weight	85 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE