


Cam follower CR18-VBUU-IKO - CR18-VBUU-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cr18-vbuu-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



CR18-VBUU

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Spigot type With groove outer ring	Spigot type With cylindrical outer ring							
11.112 ($\frac{7}{16}$)			CR 18	VBUU	85	28.575 ($\frac{11}{4}$)	15.875 ($\frac{5}{8}$)	11.112 ($\frac{7}{16}$)	$\frac{1}{2}$ -20	12.700 ($\frac{1}{2}$)	
Boundary dimensions mm(inch)						Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N		
B max	B ₂	B ₃	C ₁	g ₁	g ₂					H	r
17.3 (0.68)	25.400 ($\frac{1}{1}$)	6.350 ($\frac{1}{4}$)	0.794 ($\frac{1}{16}$)	4.762 ($\frac{3}{16}$)	3.175 ($\frac{1}{8}$)	6.350 ($\frac{1}{4}$)	1.588 ($\frac{1}{16}$)	19.050 ($\frac{3}{4}$)	17.4	13 100	22 700

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463692
Inside diameter	11.112 mm
Outside diameter	28.575 mm
Thickness	15.875 mm
Weight	85 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE